

TS-464



??????? :: ??? ?? ?? ??
 ??? ?????? :: TS-464
 ??? ???????? :: 10
 ?????: 2.26kg
 ?????? 165.00mm x 170.00mm x 226.50mm
 ??? ??????:

????? ????????

????? ????????????	Intel® Celeron® N5095 4-core/4-thread processor, burst up to 2.9 GHz
????? ??? ???? ???????????	64-bit x86
???????	8 GB SODIMM DDR4 (1 x 8 GB)
??? ?????? ??????????	4
??? ?????????? ??????????	3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
????? ??? ???? ???????	?(Not supported M.2 SSD)
????? ???????	1 x 120mm, 12VDC
????? ?????? ??????/? ??????	90W adapter, 100-240V
Total Memory Slots	2 x SODIMM DDR4
Maximum Memory Capacity	16 GB (2 x 8GB)
M.2 Drive Slots	2 x M.2 2280 PCIe Gen 3 x1 Compatible with NVMe SSD PCIe Gen 3 and above. Please refer to https://www.qnap.com/compatibility/ for compatibility.
PCIe Expansion	1 Slot 1: PCIe Gen 3 x2 Card dimensions for PCIe slot 190 x 68.9 x 18.76 mm / 7.48 x 2.71 x 0.74 inches.

Form Factor (RU)	Tower
Hardware Encryption Engine (AES-NI) old	?? (AES-NI)
Graphic Processors	Intel® UHD Graphics
Floating Point Unit	??
Hardware-accelerated Transcoding	??
Flash Memory	4GB (Dual boot OS protection)
Wake on LAN (WOL)	??
Jumbo Frame	??
USB 3.2 Gen 2 (10Gbps) Port	2 x Type-A
HDMI™ Output	1, HDMI™ 2.1 (up to 4096 x 2160 @ 60Hz)
LED Indicators	Power/Status, LAN, USB, HDD1-4
Buttons	Power, USB copy, Reset
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Consumption: Disk Standby Mode	21.618
System Warning	Buzzer
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	1500
Kensington Security Slot	??

????? ????????



