

## TS-464

???????? :: ??? ?? ??? ???

??? ?????? :: TS-464

????? ??????? :: 10

?????: 2.26kg

????????: 165.00mm x 170.00mm x 226.50mm

????? ?????:



### ????? ????????

|                         |  |
|-------------------------|--|
| ????? ????????????      | Intel® Celeron® N5095 4-core/4-thread processor, burst up to 2.9 GHz   |
| ????? ????              | 64-bit x86   |
| ???????????             |  |
| ???????                 | 8 GB SODIMM DDR4 (1 x 8 GB)  |
| ?? ?????? ????????      | 4  |
| ?? ??????? ????????     | 3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives  |
| ?? ?????? ????????      | ?(Not supported M.2 SSD)   |
| ?????                   |  |
| ????? ??????            | 1 x 120mm, 12VDC   |
| ????? ??????            | 90W adapter, 100-240V  |
| ?????/??????            |  |
| Total Memory Slots      | 2 x SODIMM DDR4  |
| Maximum Memory Capacity | 16 GB (2 x 8GB)  |
| M.2 Drive Slots         | 2 x M.2 2280 PCIe Gen 3 x1 Compatible with NVMe SSD PCIe Gen 3 and above. Please refer to <a href="https://www.qnap.com/compatibility/">https://www.qnap.com/compatibility/</a> for compatibility. |
| PCIe Expansion          | 1 Slot 1: PCIe Gen 3 x2 Card dimensions for PCIe slot?190 x 68.9x 18.76 mm / 7.48 x 2.71 x 0.74 inches.  |

|   |  |
|---|--|
| Form Factor (RU)  | Tower  |
| Hardware Encryption Engine (AES-NI) old                         | ?? (AES-NI)                                      |
| Graphic Processors  | Intel® UHD Graphics                              |
| Floating Point Unit   | ??   |
| Hardware-accelerated Transcoding                                | ??   |
| Flash Memory  | 4GB (Dual boot OS protection)                    |
| Wake on LAN (WOL)   | ??   |
| Jumbo Frame   | ??   |
| USB 3.2 Gen 2 (10Gbps) Port                                     | 2 x Type-A                                       |
| HDMI™ Output  | 1, HDMI™ 2.1 (up to 4096 x 2160 @ 60Hz)          |
| LED Indicators  | Power/Status, LAN, USB, HDD1-4                   |
| Buttons   | Power, USB copy, Reset                           |
| Operating Temperature   | 0 - 40 °C (32°F - 104°F)                         |
| Storage Temperature   | -20 - 70°C (-4°F - 158°F)                        |
| Relative Humidity   | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Consumption: Disk Standby Mode                            | 21.618   |
| System Warning  | Buzzer   |
| Max. Number of Concurrent Connections (CIFS) - with Max. Memory | 1500   |
| Kensington Security Slot  | ??   |
| ????? ????????  |  |



