

TS-832PXU-RP



???????? :: ??? ?? ??? ??
??? ?????? :: TS-832PXU-RP
???? ??????? :: 10
?????: 12.47kg
????????88.60mm x 432.00mm x 511.00mm
???? ?????:

????? ????????

| | |
|-------------------------|---|
| ????? ???????????? | AnnapurnaLabs Alpine AL324 64-bit ARM® Cortex-A57 4-core 1.7GHz processor |
| ????? ???? | 64-bit ARM |
| ??????????? | |
| ????? ???????? | ? |
| ??????? | 4 GB UDIMM DDR4 (1 x 4 GB) |
| ??? | 8 |
| ??? | 3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives |
| ????? ???? | ? (Not supported M.2 SSD) |
| ?????? | |
| ????? USB ???? | 3.2 |
| ????? ?????? | 4 |
| ????? ?????? | 2 x 70mm, 12VDC |
| ????? ?????? | 250W (x2) PSU, 100 - 240V |
| ??????/?????? | |
| Total Memory Slots | 1 x UDIMM DDR4 |
| Maximum Memory Capacity | 16 GB (1 x 16 GB) |
| M.2 Drive Slots | Optional via a PCIe adapter |
| PCIe Expansion | 1 Slot 1: PCIe Gen 2 x2 PCIe bandwidth limitations will restrict the NAS 10GbE performance. Card dimensions for PCIe slot?220 x |

| | |
|---|--|
| | 68.9x 18.76 mm / 8.67 x 2.71 x 0.74 inches. |
| Form Factor (RU) | 2U Rackmount |
| Floating Point Unit | ? |
| Flash Memory | 512 MB (Dual boot OS protection) |
| Wake on LAN (WOL) | ? Only the 2.5GbE port |
| Jumbo Frame | ? |
| LED Indicators | HDD 1-8, Status, LAN, Storage expansion |
| Buttons | Power, Reset |
| Operating Temperature | 0 - 40 °C (32°F - 104°F) |
| Storage Temperature | -20 - 70°C (-4°F - 158°F) |
| Relative Humidity | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| System Warning | Buzzer |
| Max. Number of Concurrent Connections (CIFS) - with Max. Memory | 700 |

????? ????????



