

# SIMPO



**Brand:** Teletek  
**Product Code:** SIMPO  
**Availability:** 5  
**Weight:** 4.20kg  
**Dimensions:** 81.20mm x 306.00mm x 412.00mm

**Price: \$31,000.00**

## Short Description

Teletek SIMPO 1 Loop Addressable Fire Alarm Panel

## Description

SIMPO is the perfect solution for smaller addressable installations. The addressable panel supports up to two loops with coverage of 48 zones. 250 devices operating on Teletek Electronics communication protocol could be connected to each loop. System status is visualized via LCD display and LED indication. Up to 64 Simpo panels can be connected in RS485 redundant network or Ethernet network. Direct programming with ProsTE software is available. The panel comes in a metal casing with a multilingual LCD display and front foil for easier customization.

## Specification

Fire Alarm	
Loops	2
Devices per loop	250
Zones	48
Inputs	3
Outputs (monitored, relay type)	5
Outputs (non monitored, programmable, relay type)	4
Memory LOG	10 / 240 events

Panels in RS485 redundant network (optional module)	Up to 64
Thermal printer	Optional
Display	4*40 symbols LCD
Multi language support	Yes
Programming	ProsTE software
Standard	EN54 – 2/4
Main Power Supply	90 ÷ 264 VAC
Frequency	47 ÷ 440 Hz
Back-up Power Supply	1 battery, 12V/ 18Ah
Electrical output	4.2A
Operating temperature	-5°C to +40°C

## Product Gallery

